PP600H AC PowerPack

AC/DC Converter to Supply PS2-600 and specific PS2-1800HR Pump Systems with Backup Power from a Generator or Mains Supply

ORDER INFORMATION

- **Item no.**: 19-001040 **product name**: PowerPack 600H, UL

TECHNICAL DATA

- AC input: 120V or 240V (±15 %), selectable, 47 to 63Hz
- AC input current: 6.2A (120V) or 3.1A (240V)
- PV input voltage: Vmp: 130V DC, depending on pump controller max. voltages
- PV max open circuit voltage: 200V DC depending on pump controller max. voltages
- DC output: 120V DC (no load), 700W
- Overload protection: internal fuse, 15A
- Enclosure: steel, gasket-sealed, indoor-use, hinged front cover with key-lock
- Must be protected from direct mid-day sun
- Enclosure class: IP22
- Ambient temperature: max. 45°C
- All wired must be #14 AWG (2.5 mm²) or larger
- Manual with further information is available in partnerNET
- Meets requirements for CE

Electrical Safety

MET c us LISTED CE



DIMENSION/WEIGHT

- 450 x 300 x 140 mm
  17.7 x 11.8 x 5.5 in
- Total weight: 16 kg / 35 lbs

BERNT LORENTZ GmbH
Siebenstücken 24, 24558 Henstedt-Ulzburg, Germany,
Tel +49 (0)4193 7548-0, Fax -29, www.lorentz.de

Sun. Water. Life.

V201105

All specifications and information are given with good intent, errors are possible and products may be subject to change without notice.
Pictures may differ from actual products depending on local market requirements and regulations.